

What is claimed is:

1. A face frame snap-on hinge for adjustably supporting a door on a supporting frame member, one of the members having a substantially circular bore, the hinge comprising: a frame cup adapted to be inserted into the bore; a hinge pin mounted in the hinge cup; a hinge arm having first and second ends, the first end pivotally secured to the hinge pin; a base plate releasably securable to one of the members; a door adjusting member movably secured to the base plate; and a U-shaped member associated with the door adjusting member and the base plate to selectively position the door adjusting member with the base plate and thereby selectively position the door with respect to the frame member while the hinge arm second end and the base plate remain connected.
2. The hinge as claimed in claim 1 wherein the hinge arm and U-shaped member are independently adjustable to selectively position the frame member with respect to the door.
3. The hinge as claimed in claim 1 wherein the hinge arm and adjusting member are operable to disconnect the hinge arm from the base plate.
4. The hinge as claimed in claim 1 wherein the adjusting member is releasably secured to the hinge arm and U-shaped member.
5. The hinge as claimed in claim 1 wherein the door adjustment member has a camming screw to operably control the selective positioning of the door member with respect to the frame member.
6. The hinge as claimed in claim 2 wherein the hinge arm and U-shaped member are operable to disconnect the hinge arm from the base plate.

7. The hinge as claimed in claim 2 wherein the connecting and release means is releasably secured to the hinge arm and separately and releasably secured to the door adjustment member.
8. The hinge as claimed in claim 1 wherein the base plate is selectively adjustable with the frame.
9. The hinge as claimed in claim 2 wherein the base plate is selectively adjustable with the frame.
10. The hinge as claimed in claim 3 wherein the base plate is selectively adjustable with the frame member.
11. The hinge as claimed in claim 4 wherein the base plate is selectively adjustable with the frame member.
12. The hinge as claimed in claim 11 wherein the hinge arm and the U-shaped member have aligned openings permitting independent adjustment of the door adjusting member therethrough.
13. The hinge as claimed in claim 12 wherein the camming screw is accessible through the aligned openings.
14. The hinge as claimed in 12 wherein the U-shaped member has a pair of clasping legs and the adjusting member has recesses for receiving and releasably securing the clasping legs to maintain the U-shaped member, adjusting member and hinge arm together.